

MOBILE PHONE IMPROVEMENTS

FIELD AND BACKGROUND OF THE INVENTION

The present invention is concerned with reducing radiation from a mobile phone into the brain of its user. There is concern that such radiation may possibly be harmful to parts of the brain.

Currently available mobile phones comprise a housing that includes a set of operating keys, a display at a top portion of the mobile phone, a radio frequency transceiver, an aerial at the top portion of the mobile phone, a microphone, a speaker at the top portion of the mobile phone that converts electrical speech signals into sound, and wiring for interconnecting these items. In use, the speaker is placed at the ear, with the aerial also close to or at the ear. The speaker, being a wired electrical part, radiates radio waves straight into the ear and, therefore, into the brain. All metallic parts in the mobile phone reflect or re-radiate radio waves emanating from the aerial. Also, the aerial itself is very close to the brain and therefore transmits strong radio waves into the brain.

In order to reduce the risk of radiation into the brain many users of mobile phones have resorted to using a hands-free kit. The conventional hands-free kit consists of a cable having a plug that fits into the mobile phone. The cable has a microphone part way along its length, and terminates in an earphone that is fitted to the ear. It has been supposed that the hands-free kit provides protection against radiation into the brain, since the mobile phone casing containing the transmitter can be placed away from the head, for example in a pocket. However, some tests that have been carried out indicate that the cable of the hands-free kit can guide radio waves into the

brain via the ear, in some cases causing higher radiation in portions of the brain than when the kit is not resorted to.

SUMMARY OF THE INVENTION

A mobile phone according to the present invention comprises an ear-piece for transmitting sound in a first direction; a transducer for converting electrical signals into speech sound; and a dielectric member having an acoustic duct that extends in a direction that is normal to the first direction, the acoustic duct guiding sound generated by the transducer to the ear-piece. By this, all metallic parts of the mobile phone (which parts are sources of radio frequency radiation or re-radiation) can be kept well away from the ear and brain.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates schematically a mobile phone according to a first embodiment of the invention.

FIG. 2 illustrates schematically a second embodiment of the invention, using a telescopic sound guide.

FIG. 3 illustrates schematically a third embodiment of the invention comprising a hands-free kit.

DESCRIPTION OF PREFERRED EMBODIMENTS

FIG. 1 illustrates schematically the first embodiment of the invention. As shown, mobile phone assembly 1 includes a lid 3 of dielectric material that can rotate about a hinge 4, a display screen 5, a microphone 2, and operating keys 6. Included in lid 3 is a transducer 7 that is close to hinge 4 and that converts electrical energy into sound. Speech sound from transducer 7 is transmitted via a duct 8 in lid 3 to exit from lid 3 at an opening 9 in the direction of arrow 15 into the user's ear.

Opening 9 is in a dished portion 10 of lid 3 that serves as the earpiece of the mobile phone. By this arrangement all electrical parts of the mobile phone can be kept several centimeters away from the ear. The length of the lid can range from 7cm to 15cm or more. consequently hole 9, opposite the ear, can be about 5cm to 13cm away from all metal parts of the phone. Transducer 7 is connected to circuits in mobile phone 1 by a flexible cable not shown. Sound duct 8 can have a cross section of any shape, for example the cross section can be a 2 millimeter diameter circle. Lid 3 can be made wholly or partly transparent so as to allow display 5 to be seen even if lid 3 is in the folded position, i.e. covering the display. Mobile phone casing includes an aerial and a radio frequency transmitter and receiver (not shown) for communication with base stations. The aerial may be wholly or partly inside casing 11.

During talking using mobile phone 1, earpiece 10 is pressed against the user's ear. The direction 12 in which sound is guided by duct 8 is normal to the direction of arrow 15.

If desired, transducer 7 can be placed inside casing 11 at shown location 14; in which case holes are provided at the top of casing 11 and the bottom of lid 3 so as to provide unobstructed transmission of sound from transducer 7 to duct 8.

FIG.1 shows lid 3 hinged to casing 11 so that it can swing to cover the front face of casing 11 when not in use. It is possible to re-arrange lid 3 so that it is hinged to casing 11 so as to cover the back of casing 11 when not in use.

FIG.2 illustrates schematically a second embodiment of the invention. As shown, mobile phone assembly 20 includes the transducer 7 arranged to deliver speech sound into the bottom of a cylindrical tube 21. Contained in cylindrical tube 21 is a cylindrical tube 22 of non-metallic material, and inside tube 22 is a cylindrical tube 23, also of non-metallic material. The top end of

